



Product Dimensions	Overall Thickness	6.0mm (5.0mm + 1.0mm high-density XPE underlayment)
	Width and Length	7 $\frac{1}{4}$ in. W x 60in. L
Packaging (Per Carton)	Total Weight	31 lbs.
	Total Pieces	6 pcs.
	Total Sqft.	18.23 Sqft.
Construction (Class III High Performance EVP)	Top Layers	UV Coating
		20 Mil. Wear Layer
		Advanced Hi-def Decor film
	Core	5.0mm Limestone composite, 0% Wood
	Density	1900kg/m ³ ± 10%
Pad	1.0mm XPE Underlayment	
Installation	Floating Glue-less Click	
Warranty	30 Year limited Residential / 10 Year Commercial	
Test Data		
Static Load	ASTM F970-17-----	2000 PSI
Heat Exposure Resistance F1700 (70°C / 7 days)	ASTM F1514----- EN 16511	≤0.10%
Swelling After Submersion	NALFA LF 01-2011-----	0%, Class 4, Commercial
IIC & STC	ASTM E492 / ASTM E90-----	IIC Rating =65 / STC = 61
Castor Chair Resistance	ISO 4918-----	Passes (25,000 Cycles)
Fire Rating	ASTM E648/662-----	Class I
Wear Resistance F 1700	EN 13329 Method A----- EN 16511-----	Class 33, AC4, Commercial Class 33, Commercial
Impact Resistance (Large Ball)	NALFA LF01-2011----- EN 13329-----	Class 4, Commercial IC3, Class 33, Commercial
Impact Resistance (Small Ball)	NALFA LF01-2011----- EN 13329-----	Class 4, Commercial IC3, Class 33, Commercial
Static Coefficient of Friction (Slip Resistance)	ASTM D 2047-----	Dry: .41 Wet: .56
Resistance to Staining / Chemicals (F1700)	ASTM F925----- NALFA LF01-2011-----	Pass Class 4, Commercial
Chemical Composition		
VOC	FloorScore™-----	Pass California 01350
Ortho-phthalates	Prop 65----- Compliance	In
Lead	CPSIA-----	None Detected
Substance of Very High Concern (SVHC)	(Mercury, Cadmium, Chromium VI, SCCp, Benzene, Xylene, Tributyltin, etc.)-----	Not Detected