



Product Dimensions	Overall Thickness	5.5mm (4.0mm + 1.5mm high-density XPE underlayment)
	Width and Length	7 $\frac{1}{4}$ in. W x 48in. L
Packaging (Per Carton)	Total Weight	41 lbs.
	Total Pieces	10 pcs.
	Total Sqft.	23.98 Sqft.
Construction  (Class III High Performance EVP)	Top Layers	UV Coating
		12 MIL Wear Layer
		Advanced Hi-def Decor film
	Core	4.0mm Limestone composite, 0% Wood
	Density	1900kg/m <sup>3</sup> $\pm$ 10%
Pad	1.5mm XPE Underlayment	
Installation	Floating Glue-less Click	
Warranty	30 Year limited Residential / 10 Year Commercial	
<b>Test Data</b>		
Static Load	ASTM F970-17-----	2000 PSI
Heat Exposure Resistance F1700 (70°C / 7 days)	ASTM F1514----- EN 16511	$\leq$ 0.10%
Swelling After Submersion	NALFA LF 01-2011-----	0%, Class 4, Commercial
IIC & STC	ASTM E492 / ASTM E90-----	IIC Rating =65 / STC = 61
Castor Chair Resistance	ISO 4918-----	Passes (25,000 Cycles)
Fire Rating	ASTM E648/662-----	Class I
Wear Resistance	EN 13329 Method A-----	Class 33, AC4, Commercial
F 1700	EN 16511-----	Class 33, Commercial
Impact Resistance (Large Ball)	NALFA LF01-2011-----	Class 4, Commercial
	EN 13329-----	IC3, Class 33, Commercial
Impact Resistance (Small Ball)	NALFA LF01-2011-----	Class 4, Commercial
	EN 13329-----	IC3, Class 33, Commercial
Static Coefficient of Friction (Slip Resistance)	ASTM D 2047-----	Dry: .41
		Wet: .56
Resistance to Staining / Chemicals (F1700)	ASTM F925-----	Pass
	NALFA LF01-2011-----	Class 4, Commercial
<b>Chemical Composition</b>		
VOC	FloorScore™-----	Pass California 01350
Ortho-phthalates	Prop 65----- Compliance	In
Lead	CPSIA-----	None Detected
Substance of Very High Concern (SVHC)	(Mercury, Cadmium, Chromium VI, SCCp, Benzene, Xylene, Tributyltin, etc.)---- <b>Not Detected</b>	