

Specifications

Construction: High Density

Fiberboard

Edge Type: Beveled

Thickness: 12.3mm

Nominal Length: 48"

Nominal Width: 6-1/2"

Coverage per Carton: 22.25 ft²

Pieces per Carton: 10

Weight per Carton: 41 lbs.

Installation Method: Floating

Recommended Usage: Residential

Underlayment Required: Yes

Waxed Edges: No

Locking System: Valinge Drop-Lock



This product is protected by a 35 year residential warranty and a 5 year limited commercial warranty



Abrasion Class 3 Rating works well in all areas of the home and can withstand normal household traffic




This floor is compliant with Phase 2 emissions standards of the California Air Resources Board.

This collection provides a distressed finish making it look almost identical to real wood.

Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance


Recommended Underlayment



2mm or
3mm Blue



2mm or
3mm Silver



EVA



Rubber



1/4 Cork



1/2 Cork

Accessories

MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding