



Product Dimensions	Overall Thickness	5.0mm (3.5mm + 1.5mm high-density EVA underlayment)
	Width and Length	7in. W x 48in. L
Packaging (Per Carton)	Total Weight	38 lbs.
	Total Pieces	12 pcs.
	Total Sqft.	29.74 Sqft.
Construction  (Class III High Performance EVP)	Top Layers	UV Coating
		12 Mil. Wear Layer
		Advanced Hi-def Decor film
	Core	3.5mm Limestone composite, 0% Wood
	Density	1900kg/m <sup>3</sup> ± 10%
Pad	1.5mm EVA Underlayment	
Installation	Floating Glue-less Click	
Warranty	30 Year limited Residential / 10 Year Commercial	
<b>Test Data</b>		
Static Load	ASTM F970-17-----	2000 PSI
Heat Exposure Resistance F1700 (70°C / 7 days)	ASTM F1514----- EN 16511	≤0.10%
Swelling After Submersion	NALFA LF 01-2011-----	0%, Class 4, Commercial
IIC & STC	ASTM E492 / ASTM E90-----	IIC Rating =65 / STC = 61
Castor Chair Resistance	ISO 4918-----	Passes (25,000 Cycles)
Fire Rating	ASTM E648/662-----	Class I
Wear Resistance F 1700	EN 13329 Method A----- EN 16511-----	Class 33, Commercial Class 33, Commercial
Impact Resistance (Large Ball)	NALFA LF01-2011----- EN 13329-----	Class 4, Commercial IC3, Class 33, Commercial
Impact Resistance (Small Ball)	NALFA LF01-2011----- EN 13329-----	Class 4, Commercial IC3, Class 33, Commercial
Static Coefficient of Friction (Slip Resistance)	ASTM D 2047-----	Dry: .41 Wet: .56
Resistance to Staining / Chemicals (F1700)	ASTM F925----- NALFA LF01-2011-----	Pass Class 4, Commercial
<b>Chemical Composition</b>		
VOC	FloorScore™-----	Pass California 01350
Ortho-phthalates	Prop 65-----	In Compliance
Lead	CPSIA-----	None Detected
Substance of Very High Concern (SVHC)	(Mercury, Cadmium, Chromium VI, SCCp, Benzene, Xylene, Tributyltin, etc.)----- <b>Not Detected</b>	