

## Specifications

Construction: Engineered Black Core  
 High-Density Fiber Board Edge Type:  
 V-Groove Beveled Thickness: 12.3mm  
 Nominal Length: 24" - 48" - 72"  
 Nominal Width: 7-3/4"  
 Coverage per Carton: 22.99 ft<sup>2</sup>  
 Pieces per Carton: 9  
 Weight per Carton: 46 lbs.  
 Installation Method: Floating  
 Recommended Usage: Residential  
 Underlayment Required: Yes Waxed  
 Edges: Yes - triple moisture waxed edge protection  
 Locking System: Valinge Drop-Lock



This product is protected by a 30 year residential warranty and a 10 year limited commercial warranty



Abrasion Class 4 Rating works well in all areas of the home and can withstand normal household traffic



This floor is compliant with Phase 2 emissions standards of the California Air Resources Board.


\*Waterproofing performance: absorbed ±5% of core density when fully submerged in water for 36 hours

i. This product is 99% waterproof constant water / moisture exposure will cause the flooring to warp or buckle over extended periods of time.

## Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance


## Recommended Underlayment



2mm or 3mm Blue



2mm or 3mm Silver



EVA



Rubber



¼ Cork



½ Cork

## Accessories

