

Specifications

Construction: Engineered Black Core High-

Density Fiber Board

Edge Type: V-Groove Beveled

Thickness: 12.3mm core + 2mm antimicrobial pad attached

Nominal Length: 60"

Nominal Width: 9.33"

Coverage per Carton: 19.33 ft²

Pieces per Carton: 8

Weight per Carton: 52 lbs.

Installation Method: Floating

Recommended Usage: Residential

Underlayment Required: Yes - moisture barrier required

Waxed Edges: Yes - triple moisture waxed edge protection

Locking System: Valinge Drop-Lock

IIC Rating: 59

STC Rating: 61



This product is protected by a 30 year residential warranty and a 10 year limited commercial warranty



Abrasion Class 4 Rating works well in all areas of the home and can withstand normal household traffic



This floor is compliant with Phase 2 emissions standards of the California Air Resources Board.


*Waterproofing performance: absorbed ±5% of core density when fully submerged in water for 300 hours

- i. This product is 99% waterproof constant water / moisture exposure will cause the flooring to warp or buckle over extended periods of time.

Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance


Recommended Underlayment



2mm or 3mm Blue



2mm or 3mm Silver



EVA



Rubber



¼ Cork



½ Cork

Accessories

MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding