



Product Dimensions	Overall Thickness	8.0mm (6.0mm + 2.0mm EVA High Density Underlayment)
	Width and Length	9.0" W. x 60.0" L
Packaging (Per Carton)	Total Weight	51 lbs.
	Total Pieces	7 pcs.
	Total Sqft.	19.07 Sqft.
Construction (Class III High Performance EVP)	Top Layers	UV Coating
		30 Mil. Wear Layer
		Advanced Hi-def Decor film
	Core	6.0mm Limestone composite, 0% Wood
	Density	1900kg/m ³ ± 10%
Pad	2.0mm EVA High Density Underlayment	
Installation	Floating Glue-less – Valinge 5G	
Warranty	Lifetime limited Residential / 10 Year Commercial	
Test Data		
Static Load	ASTM F970-17-----	2000 PSI
Heat Exposure Resistance F1700 (70°C / 7 days)	ASTM F1514----- EN 16511	≤0.10%
Swelling After Submersion	NALFA LF 01-2011-----	0%, Class 4, Commercial
IIC & STC	ASTM E492 / ASTM E90-----	IIC Rating =64 / STC = 61
Castor Chair Resistance	ISO 4918-----	Passes (25,000 Cycles)
Fire Rating	ASTM E648/662-----	Class I
Wear Resistance F 1700	EN 13329 Method A----- EN 16511-----	Class 33, AC4, Commercial Class 33, Commercial
Impact Resistance (Large Ball)	NALFA LF01-2011----- EN 13329-----	Class 4, Commercial IC3, Class 33, Commercial
Impact Resistance (Small Ball)	NALFA LF01-2011----- EN 13329-----	Class 4, Commercial IC3, Class 33, Commercial
Static Coefficient of Friction (Slip Resistance)	ASTM D 2047-----	Dry: .41 Wet: .56
Resistance to Staining / Chemicals (F1700)	ASTM F925----- NALFA LF01-2011-----	Pass Class 4, Commercial
Chemical Composition		
VOC	FloorScore™-----	Pass California 01350
Ortho-phthalates	Prop 65-----	In Compliance
Lead	CPSIA-----	None Detected
Substance of Very High Concern (SVHC)	(Mercury, Cadmium, Chromium VI, SCCp, Benzene, Xylene, Tributyltin, etc.)----- Not Detected	