



Specifications

Construction: Engineered Black Core High-Density Fiber Board
 Edge Type: V-Groove Beveled
 Thickness: 10mm core + 2mm antimicrobial pad attached
 Nominal Length: 60"
 Nominal Width: 9.0"
 Coverage per Carton: 24.8 ft²
 Pieces per Carton: 8
 Weight per Carton: 52 lbs.
 Installation Method: Floating
 Recommended Usage: Residential
 Underlayment Required: Yes - moisture barrier required
 Waxed Edges: Yes - triple moisture waxed edge protection
 Locking System: Valinge Drop-Lock
 IIC Rating: 55
 STC Rating: 58



This product is protected by a 30 year residential warranty and a 10 year limited commercial warranty



Abrasion Class 4 Rating works well in all areas of the home and can withstand normal household traffic



This floor is compliant with Phase 2 emissions standards of the California Air Resources Board.


*Waterproofing performance: absorbed ±5% of core density when fully submerged in water for 300 hours

- i. This product is 99% waterproof constant water / moisture exposure will cause the flooring to warp or buckle over extended periods of time.

Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance

Recommended Underlayment



2mm or 3mm Blue



2mm or 3mm Silver



EVA



Rubber



¼ Cork



½ Cork

Accessories

