



AAT Laminate Flooring

Specifications

Construction: Engineered Black Core High-Density Fiber Board
 Edge Type: V-Groove Beveled
 Thickness: 12.3mm core (no pad attached)
 Nominal Length: 23.62"
 Nominal Width: 3.93"
 Coverage per Carton: 23.25 ft²
 Weight per Carton: 51.8 lbs.
 Installation Method: Floating
 Recommended Usage: Residential
 Underlayment Required: Yes + moisture barrier required
 Waxed Edges: Yes - triple moisture waxed edge protection
 IIC Rating: 58
 STC Rating: 60
 Locking profile: This collection features A and B sided planks.



This product is protected by a 30 year residential warranty and a 10 year limited commercial warranty

Abrasion Class 4 Rating suitable for Limited Commercial and all Residential Applications



This floor is compliant with Phase 2 emissions standards of the California Air Resources Board.


*Waterproofing performance: absorbed ±5% of core density when fully submerged in water for 300 hours

i. This product is 99% waterproof constant water / moisture exposure will cause the flooring to warp or buckle over extended periods of time.

Features

- UV Resistant
- Fire Resistant
- Scratch Resistant
- Slip Resistant
- Stain Resistant
- Fade Resistant
- Hypoallergenic
- Non Toxic
- Mildew Resistant
- Easy Maintenance


Recommended Underlayment



2mm or 3mm Blue



2mm or 3mm Silver



EVA



Rubber



¼ Cork



½ Cork

Accessories

